

Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enquiries@ltslab.co.uk www.ltslab.co.uk



9630

23/04/2021

## **TEST CERTIFICATE**

CLIENT: Supplied by: Certificate Number: UK2100491 -1

Vyva Fabrics

TT. Vasumweg 140 Date Received: 1033 SH Amsterdam

The Netherlands Date Issued: 27/04/2021

Issue Number: 1

Changes from previous issue (if applicable)

**Tel:** +31 (0) 20 659 9523 **Email:** info@vyvafabrics.nl

## SAMPLE IDENTIFICATION

The information is this section is provided by the client and Lancashire Testing Services Ltd assumes no reponsibility or liability for its accuracy.

Sample Name / Reference Agua Fabrics Finezza

Additional Names: -

Batch Ref/Number: Order Number: -

Colour: -

Fabric Composition: 100% Polyester

Customer: Vyva Fabrics

## **SPECIFICATION**

BS7176:2007 + A1:2011 - Medium Hazard

**TEST METHOD** 

Flammability: BS EN 1021-1:2006 Part 1: Ignition source smouldering cigarette

BS EN 1021-2:2006 Part 2: Ignition source match flame equivalent

BS 5852:2006 Crib Ignition source 5

Pre-treatment: BS 5852:2006 Annex E - Water soaking procedure

## **Conclusion**

The composite tested: **Complies** with the flammability requirements of: BS 7176:2007 + A1:2011 Medium hazard, taking into account uncertainty of measurement. Uncertainty of Measurement: ±1 second - timing measurements, ±1mm - dimensional measurements

**Comments:** 

Please note that copies of this original certificate are not valid



Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enquiries@ltslab.co.uk www.ltslab.co.uk



9630

# **TEST CERTIFICATE**

Tost E	Poeulte:-							-		
	Test Results:-									
BS7176:2007 + A1:2011 - Medium Hazard - Specification for resistance to ignition of upholstered furniture for non-domestic seating by testing composites										
						terials under the particular cond	litions of test: t	they are not		
			g the full potential				miorio di todi, t	are met		
Sample	Code		UK2100491 -1							
Sample / Name Reference			Agua Fabrics Finezza							
Client			Vyva Fabrics							
Date of test			27/04/2021							
Pre-Treatment			BS 5852:2006 Annex E - Water soaking procedure							
			Line Dried during day at ambient temperature							
Filling Type			Carpenter/RX36110 CMHR polyurethane foam of approximate density 36Kg/m3							
Size of test rig			Small: Back - 450 x 300 ± 2mm + Seat - 450 x 150 ± 2mm							
Test Conditions			Period h	Tempe	rature ºC	Relative humidity % Air Flow m/s Volu		Volume m <sup>3</sup>		
Conditioning of test specimens			≥24	23±2		50±5	-	-		
Testing conditions			-	10	)-30	15-80 0.02-0.2				
Testing Source			BS EN 1021-1:2006 Smouldering Cigarette Source							
Testing time limit			60 minutes after placement of smouldering cigarette.							
Test	Position	Ignition/N on Ignition	Duration of: (min.sec)							
No.			Ignition Source	Flames	Smoke	Smouldering and flaming criteria exceeded: (If an				
1	LHS	NI	21.34	-	21.59	-				
2	М	NI	21.31	-	21.54	-				
3	-	-	-	-	-	-				
Testing Source			BS EN 1021-2:2006 Match flame ignition source							
Testing time limit			2 minutes after removal of burner tube (120 seconds)							
Test	Position	Ignition/N on Ignition	Duration of: (sec)							
No.			Ignition Source	Flames	Smoke	Smouldering and flaming criteria exceeded: (If any)				
1	LHS	NI	15	15	21	-				
2	М	NI	15	15	23	-				
3	RHS	NI	15	15	25	-				
RESUI	LT:	SMOULI	DERING CIGARETTE SOURCE				PASS			
	MATCH FLAME IGNITION SOURCE						P/	\SS		
KEY: I = Ignition, NI = Non Ignition, LHS = Left hand side, M = Middle, RHS = Right hand side										

Issue Number: 1

Please note that copies of this original certificate are not valid



Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enquiries@ltslab.co.uk www.ltslab.co.uk



9630

# **TEST CERTIFICATE**

Test Results:- BS7176:2007 + A1:2011 - Medium Hazard - Specification for resistance to ignition of upholstered										
furniture for non-domestic seating by testing composites										
	-		nly to the ignitabilg the full potential	-			e particular cond	itions of test;	they are not	
Sample Code			UK2100491 -1							
Sample Reference			Agua Fabrics Finezza							
Client			Vyva Fabrics							
Date of test			27/04/2021							
Pre-Treatment			BS 5852:2006 Annex E - Water soaking procedure							
			Line Dried during day at ambient temperature							
Filling Type			Carpenter/RX36110 CMHR polyurethane foam of approximate density 36Kg/m3							
Size of test rig			Large: Back - 450 x 450 ± 2mm + Seat - 450 x 300 ± 2mm							
Test Conditions			Period h	Tempe	rature ⁰C	Relative humidity %		Air Flow m/s	Volume m <sup>3</sup>	
Conditioning of test specimens			≥24	23	3±2	50±5		-	-	
Testing conditions			-	10	0-30 15-80		0.02-0.2	≥6		
Testing Source			BS 5852:2006 Crib Ignition source 5							
Testing time limit			10 minutes after ignition of crib. Observed for 60 minutes in total.							
Test	Position	Ignition/N	Duration of:	(min.sec)	Extent of Damage to component: mm					
No.		on Ignition	Flames	Smoke	Horizontal			Vertical		
		ignition			Width	Length	Depth	Width	Depth	
1	М	NI	5.16	7.17	169	121	49	180	55	
2	М	NI	4.26	7.44	169	125	51	176	54	

Test No.	Time for: (sec)						
	Ignition of test pieces	Cover Splitting	Extinction				
1	-	-	-				
2	-	-	-				

KEY: I = Ignition, NI = Non Ignition, LHS = Left hand side, M = Middle, RHS = Right hand side

**CRIB IGNITION SOURCE 5** 

On behalf of Lancashire Testing Services:

Tony Alcock, Laboratory Technician:

Laboratory Technician:

John Marsh, Laboratory Technician: Peter Collings, Operations Manager:

**PASS** 

Please note that copies of this original certificate are not valid

Issue Number: 1

**RESULT:** 



Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enquiries@ltslab.co.uk www.ltslab.co.uk



# **TEST CERTIFICATE**

Certificate Number: UK2100491-1

If the measurement result plus/minus the expanded uncertainty with a 95 % coverage probability overlaps the limit, it is not possible to state compliance or non-compliance. The measurement result and the expanded uncertainty with a 95 % coverage probability will then be reported. The report will include the actual value with the uncertainty range.

Lancashire Testing Services Ltd have conducted thorough analysis of the uncertainty of all measurements carried out in the application of the standard or standards detailed in this report. Where possible any associated uncertainty of measurements have been accounted for in the working instructions, so that they have no impact on the reporting of the final result. In instances were uncertainty of measurements can only be taken into account after the test has been conducted, these uncertainty values have been stated on this report. The stated uncertainty of measurement has also been taken into account in the final reporting of the overall result.

**Issue Number: 1** 

Please note that copies of this original certificate are not valid