

Supplied by:  
**Vyva Fabrics**  
**TT. Vasumweg 140**  
**1033 SH Amsterdam**  
**The Netherlands**

**TN # : 128**  
**Date : 19/2/2023**  
**Revision: 4**

**Product Description : Colorways 5**

756 g/m<sup>2</sup> Total weight, 1371.6 mm. finished width, Cotton 100%, PreFixx top finish, Roll size 27 meters.  
 Phthalate Free - 6P

<b>General</b>		
Total Wt. - g/m <sup>2</sup> . (ISO 2286)		756 ± 10%
Width - mm. (Min.) (ISO 2286)		1371.6 (-0,+25.4)
Gauge (Mils)		
(mm.)		1.10 ± 10%
Face Content		PVC
Plasticizer		20 - 40%
Phthalate Free		6P
<b>Substrate</b>		
Construction		JERSEY
Content		Cotton 100%
<b>Adhesion (ISO 2411)</b>		
N./5cm.	MD	26 min
	TD	26 min
<b>Ultimate Tensile Strength (CFFA-17)</b>		
Pounds	MD	45 min
	TD	45 min
<b>Ultimate Tensile Elongation (CFFA-17)</b>		
%	MD	40 min
	TD	100 min
<b>Stretch (ISO 7617-1:1994(E) Annex B)</b>		
%	MD	10 min
	TD	40 min
<b>Set (ISO 7617-1:1994(E) Annex B)</b>		
%	MD	33 max
	TD	33 max
<b>Tack Strength (Stich)</b>		
	MD	
	TD	
<b>Abrasion</b>		
	MD	
	TD	
<b>Blocking (ISO 5978)</b>		
		Separation without damage to surface
<b>W-Flex</b>		
<b>Bursting Strength</b>		

<b>UV</b>		
QUV ( UVA 340 Bulb)	(CFFA-2)	70 hrs- No Change
<b>Mildew Resistance - ASTM G-21</b>		
		No growth
<b>Cold Crack</b>		
Roller Temperature		
<b>Prefix Stain Test (CTM)</b>		
		Pass
<b>Unsupported Film</b>		
Dimensional Stability		
Specific Gravity		
Modulus		
Shrinkage		
Plasticizer (PHR)		
<b>Flame Retardancy</b>		
FMVSS-302		
NFPA 701 Small Scale		
NY/NJ Port of Authority		
California Tech. Bulletin 117		
Fed. Std. A-A-2950 (Supercedes)		
Vertical Flame (CCC-A-680A)		After burn avg. 2 sec.max Char length 4" max
FAR 25.853B		
BIFMA		
Boston Fire Dept. IX-1		
UFAC Fabric, Class 1		
BS 5852 Part 1		
		Pass
<b>Additional Requirements</b>		
Color Spec		
Opacity		
Pre-Shipment Sample Required?		
Special Packaging		
<b>Outside Processes</b>		
Perforated		
Foam Lamination		
Di-eliticly Sealed (Embossed)		
Laminated (Textiles or other film)		
Laminated (Wood)		
<b>Application - Indoor/Outdoor</b>		
		Indoor
<b>Finish Type</b>		
		PreFixx