

78021 40 MINERAL



78012 40 WHITE



78014 40 FIRE RED



78016 40 NAVY



78015 40 AQUAMARINE




78018 40 CHARCOAL GREY



78022 40 PARCHMENT



78013 40 ANTIQUE BEIGE



78020 40 DOVE GREY



78017 40 LIGHT GREY



78019 40 SLATE BLACK







CHARACTERISTICS

INDOOR - OUTDOOR

Composition: Backing:	100% Solution Dyed Acryl 76% Solution Dyed Acryl / 24% Polyester
Weight:	500 g/m²
Roll Width:	min. 142 cm
Roll Length:	+/- 30 m
Colour Fastness UV:	7/8 ISO 105 B04 (Blue Wool Scale)
Shrinkage water 40 °C:	Warp <± 1,60% Weft <± 1,90% ISO 5077
Abrasion Resistance:	25000 cycles UNI EN ISO 12947-2

FINISHES AND TREATMENTS

Water Repellent Stain Resistant Mold and Mildew Resistant UV Resistant

SUSTAINABILITY

REACH

CARE AND CLEANING 🖼 🛆 🛛 🖂

For optimum care and cleaning please read the following instructions and recommendations.

Cleaning instructions

Brush off dirt before it becomes embedded in the fabric and wipe up spills or clean soon after a stain occurs. The quicker you clean spills and stains, the easier they can be to remove.

- Blot (don't rub) liquid spills with a clean, dry cloth.
 For oil-based spills, apply an absorbent such as corn starch, then remove with a straight edge.
- Spray on a mild cleaning solution of soap (such as Dawn or Woolite) and water.
- Rinse the fabric thoroughly to remove all soap residue.
- Air dry.

Tex'Aktiv Clean: Deep-acting, Powerful stain remover. Tex'Aktiv Guard: Stain protection, Beading effect.

SAMPLES AND ENQUIRES

samples: samples@vyvafabrics.nl | **orders**: info@vyvafabrics.nl

















