

# HARVEST

## Technical sheet

| CHARACTERISTICS | VALUES |      | UNITS | STANDARDS |
|-----------------|--------|------|-------|-----------|
|                 | WARP   | WEFT |       |           |

### GENERAL CHARACTERISTICS

|                  |   |                  |            |
|------------------|---|------------------|------------|
| Composition      | 28% Recycled Sunbrella Acrylic 70% Sunbrella Acrylic 2% Polyester |                  |            |
| Backing / Finish | Non PFAS - Water-repellent & Stain-proof                          |                  |            |
| Weave            | Jacquard  |                  | ISO 7211-1 |
| Weight           | 590   | g/m <sup>2</sup> | ISO 3801   |
| Width            | 140   | cm               | EN 1773    |
| Roll length      | 25  | ml               |            |

### FABRIC RESISTANCE

|                                |      |       |           |             |
|--------------------------------|------|-------|-----------|-------------|
| Tensile strength               | 118  | 113   | daN/5cm   | ISO 13934-1 |
| Elongation at break            | 22   | 29    | %         | ISO 13934-1 |
| Pilling                        | 5    |       | Class / 5 | ISO 12945-2 |
| Spray test                     | 4    |       | Class / 5 | ISO 4920    |
| Seam slippage (180 N)          | < 0  | < 0.4 | mm        | ISO 13936-2 |
| Stitching strength             | 610  | 560   | N         | ISO 13935-2 |
| Stability on 30 deg. C washing | -2.6 | 0     | %         | ISO 5077    |

### COLOUR-FASTNESS

|                                      |     |  |           |             |
|--------------------------------------|-----|--|-----------|-------------|
| Colour fastness UV - outdoor - 1000h | 4-5 |  | Class / 5 | ISO 105 B04 |
| Colour fastness UV - indoor          | 8   |  | Class / 8 | ISO 105 B02 |
| Colour fastness under dry friction   | 5   |  | Class / 5 | ISO 105X12  |
| Colour fastness under wet friction   | 5   |  | Class / 5 | ISO 105X12  |
| Colour fastness 30°C washing         | 5   |  | Class / 5 | ISO 105 C06 |

### FIRE RESISTANCE

|   |      |
|---|------|
| California Technical Bulletin 117-203 Section 1 | PASS |
| NFPA 260 Classe I                               | PASS |
| NF EN 1021-1                                    | PASS |
| BS 5852 Part 1 Source 0                         | PASS |

### USES

|                  |          |       |
|------------------|----------|-------|
| Guarantee        | 5        | years |
| Recommended Uses | Cushions |       |

### CARE



This product's values may vary with a tolerance of ± 5%

**VYVA**  
FABRICS

INDOOR & OUTDOOR  
CONTRACT FURNITURE FABRICS

VYVA FABRICS  
TT, VASUMWEG 140  
1033 SH AMSTERDAM THE NETHERLANDS  
TEL +31 (0)20 6599523 INFO@VYVAFABRICS.NL  
WWW.VYVAFABRICS.NL

 sunbrella®

 **REACH**  
COMPLIANCE

 **STANDARD 100**  
CQ 638/8  
IFTH

WARRANTY  
**5**  
YEARS

WARRANTY  
MASS  
DYED  
COLOURS

MADE IN  
  
FRANCE

 **GREENGUARD**  
PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818  
GOLD

**NON  
PFAS**