

# WANDER

## Technical sheet

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

### GENERAL CHARACTERISTICS

Composition	100% Sunbrella Acrylic		
Backing / Finish	Non PFAS - Water-repellent & Stain-proof		
Weave	Jacquard		ISO 7211-1
Weight	470	g/m <sup>2</sup>	ISO 3801
Width	140	cm	EN 1773
Roll length	35	ml	

### FABRIC RESISTANCE

Tensile strength	87	200	daN/5cm	ISO 13934-1
Elongation at break	16.4	29.8	%	ISO 13934-1
Pilling	4		Class / 5	ISO 12945-2
Spray test	5		Class / 5	ISO 4920
Seam slippage (180 N)	< 1.67	<1	mm	ISO 13936-2
Stitching strength	520	410	N	ISO 13935-2
Stability on 30 deg. C washing	+/-2	+/-1	%	ISO 5077

### COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 30°C washing	5		Class / 5	ISO 105 C06

### FIRE RESISTANCE

California Technical Bulletin 117-203 Section 1	Pass
NFPA 260 Classe I	Pass
NF EN 1021-1	Pass
BS 5852 Part 1 Source 0	Pass

### USES

Guarantee	5	years
Recommended Uses	Seating, Cushions, Curtains	

### CARE



This product's values may vary with a tolerance of ± 5%



**VYVA**  
FABRICS  
INDOOR & OUTDOOR  
CONTRACT FURNITURE FABRICS

VYVA FABRICS  
TT, VASUMWEG 140  
1033 SH AMSTERDAM THE NETHERLANDS  
TEL +31 (0)20 6599523 INFO@VYVAFABRICS.NL  
WWW.VYVAFABRICS.NL