

SUNBRELLA PLUS PU

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella® Acrylic			
Backing / Finish	Water repellent treatment - easy to clean. Polyurethane coating one side water and UV - resistant			
Weave	Canvas			ISO 7211-1
Weight	320	g/m ²		ISO 3801
Width	152	cm		EN 1773
Roll length	50	ml		

FABRIC RESISTANCE

Tensile strength	140	130	daN/5cm	ISO 13934-1
Elongation at break	30	15	%	ISO 13934-1
Tear strength	3.30	2.50	daN	ISO 13937-1
Schmerber	1000		mm	ISO 811
Spray test	4		Class / 5	ISO 4920

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5	Class / 5	ISO 105 B04
Colour fastness UV - indoor	7-8	Class / 8	ISO 105 B02
Colour fastness under dry friction	5	Class / 5	ISO 105X12
Colour fastness under wet friction	5	Class / 5	ISO 105X12

USES

Guarantee	5	years	
Recommended Uses	Sprayhood, Rear enclosure, Bimini top, Cockpit enclosure, Windscreen cover, Dodger, Console cover, Lazybag		

This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK



**STANDARD
100**
CQ 638/8
IFTH



VYVA FABRICS
TT. VASUMWEG 140
1033 SH AMSTERDAM THE NETHERLANDS
TEL +31 (0)20 6599523 INFO@VYVAFABRICS.NL
WWW.VYVAFABRICS.NL