CHARACTERISTICS

INDOOR - OUTDOOR

Composition:	100% Sunbrella Solution Dyed Acryl
Weight:	490 gr/m²
Roll Width:	min. 137 cm
Roll Length:	+/- 36,5 m
Vertical repeat: Horizontal repeat:	45,72 cm 35,56 cm
Colour Fastness UV: Colour Fastness Rain:	7/8 ISO 105 B02 7/8 ISO 105 B04

Flame retardancy*: US UFAC Interior Fabrics Test Method-1990 - Class 1 US CA 117-2013 Sec. E (CS-191-53) - Class 1

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behaviour of this or any other material under actual fire conditions.

FINISHES AND TREATMENTS

Exclusive water repellent finish

REVERSIBLE

Can be used both sides



For optimum care and cleaning please read the following instructions and recommendations.

Cleaning instructions

Brush off dirt before it becomes embedded in the fabric and wipe up spills or clean soon after a stain occurs. The quicker you clean spills and stains, the easier they can be to remove.

- Blot (don't rub) liquid spills with a clean, dry cloth. For oil-based spills, apply an absorbent such as corn starch, then remove with a straight edge.
- Spray on a mild cleaning solution of soap (such as Dawn or Woolite) and water.
- Rinse the fabric thoroughly to remove all soap residue.

Tex'Aktiv Clean: Deep-acting, Powerful stain remover. Tex'Aktiv Guard: Stain protection, Beading effect.

SAMPLES AND ENQUIRES

samples: samples@vyvafabrics.nl orders: info@vyvafabrics.nl



8001240 **ROSE**



10234 SF NATTE **FLAMINGO**



3967 SF SOLIDS MINT



3970 SF SOLIDS LICHEN



3965 SF SOLIDS BLUSH



3989 SF SOLIDS OPERA



10151 SF NATTE **LINEN CHALK**



















